



Pierret

Since 1925

a new
generation



R45

REINFORCED GUILLOTINE
CUTTING MACHINE
FOR SPECIAL FIBERS

MAIN FEATURES

- > This cutting machine is equipped with a tungsten carbide mobile knife to cut special fibers such as glass, carbon, aramid fibers, ...
- > Cutting width: 450 mm ($\pm 18''$) effective for a 830 mm ($\pm 33''$) table infeed width.
- > Acceptable compressed material thickness: 75 mm ($\pm 3''$) according to the type of material.
- > Maximum material thickness at infeed: ± 100 mm ($\pm 4''$) according to material compressibility.
- > Cutting speed: 380 cuts/min.
- > Range of cutting lengths: from 6 mm ($\pm 0.2''$) to 125 mm ($\pm 5''$). From 3 mm ($\pm 0.1''$) as an option.

- > Production varies according to the material, cutting length, loading, ... , and may reach over 1,000 kg/hour (2,200 Lbs/hour).
- > The cutting machine is driven by two three phase asynchronous motors with IP55 protection.

DESIGN

- > Simple, accurate knife adjustment via two detachable handles located on the front panel of the machine.
- > Quick and separate rolls adjustment to enable a suitable infeed gap for the materials to be cut.
- > Quick cutting length adjustment by frequency inverter.

PRACTICAL ADVANTAGES

- > Minor wear of the cutting edge can be taken up in seconds while the machine is working.
- > All PIERRET knives are straight and can be sharpened on a separate grinding machine, ideally one manufactured by PIERRET.
- > A control station used to control the machine functions is centrally located. The user can therefore work from the right- or the left-hand side of the machine.
- > Quick dismantling of the feed table.
- > A special feed table design totally eliminates penetration of foreign material between the conveyor belt and the sides.
- > The cutting machine is mounted on retractable wheels.
- > The feeding may be reversed by the simple push of a button.
- > Easy to clean under the feeding belt.
- > Easy to clean the inside of the machine.
- > Easy access to the entire transmission of the machine.

OPERATION


- > The material is conveyed on a feeding belt to an awaiting hardened steel roll assembly. The rolls compress the material on the feed table and draw it efficiently towards the knives.
- > The scissor effect produced between the carbide mobile knife and the fixed knife guarantees a clean edged cut easily and accurately.
- > The roll adjustments enable a trouble-free feeding of materials of various types and shapes.
- > Automatic feeding shutdown in over thickness conditions with withdrawal facility by feeding reversal.
- > The machine stops automatically in case of a material wrap-up.

Total installed power

- 10.8 Kw/50 Hz

Dimensions/Weight

- **R45 standard**
3,700 x 1,080 x height 1,330 mm/1,870 Kg
12'-1" x 3'-6" x height 4'-4"/4,120 Lbs
- **R45 with detector**
4,200 x 1,080 x height 1,330 mm/2,015 Kg
13'-9" x 3'-6" x height 4'-4"/4,440 Lbs



This description of the machines' technical features is provided purely for guidance and does not commit us. Modifications and improvements may be made without prior notice and at any time.

PIERRET INDUSTRIES

Rue du Sommet 32 • B-6838 CORBION • BELGIUM
Tel. (32) 61.46.51.00 • Fax. (32) 61.46.62.63

Sales & Services for U.S. and Canada

PIERRET NORTH AMERICAN DIVISION

215 Wingo Heights Rd • SPARTANBURG, S.C. 29303 • USA
Tel. (1) 864.583.4829 • Fax. (1) 864.583.3362

E-mail : info@pierret.com • Web : www.pierret.com

